

---

# NextPolish Documentation

*Release latest*

Jul 07, 2022



<b>1</b>	<b>Installation</b>	<b>3</b>
<b>2</b>	<b>Quick Start</b>	<b>5</b>
<b>3</b>	<b>Getting Help</b>	<b>7</b>
<b>4</b>	<b>Copyright</b>	<b>9</b>
<b>5</b>	<b>Cite</b>	<b>11</b>
<b>6</b>	<b>Limitations</b>	<b>13</b>
<b>7</b>	<b>Star</b>	<b>15</b>
<b>8</b>	<b>Tutorial</b>	<b>17</b>
8.1	Polishing using short reads only . . . . .	17
8.2	Polishing using long reads only . . . . .	19
8.3	Polishing using short reads and long reads . . . . .	20
8.4	Polishing using short reads and hifi reads . . . . .	20
<b>9</b>	<b>NextPolish Parameter Reference</b>	<b>23</b>
9.1	Input . . . . .	23
9.2	Output . . . . .	24
9.3	Options . . . . .	24
<b>10</b>	<b>Frequently Asked Questions</b>	<b>27</b>
10.1	What is the difference between NextPolish and Pilon? . . . . .	27
10.2	Which job scheduling systems are supported by NextPolish? . . . . .	27
10.3	How to continue running unfinished tasks? . . . . .	28
10.4	How to set the <i>task</i> parameter? . . . . .	28
10.5	How many iterations to run NextPolish cyclically to get the best result? . . . . .	28
10.6	Why does the contig N50 of polished genome become shorter or why does the polished genome contains some extra N? . . . . .	28
10.7	What is the difference between bwa or minimap2 to do SGS data mapping? . . . . .	28
10.8	How to specify the queue/cpu/memory/bash to submit jobs? . . . . .	28
<b>11</b>	<b>Performance comparison between NextPolish, Pilon and Racon using simulated short reads</b>	<b>29</b>

<b>12</b>	<b>Performance comparison between NextPolish and Racon using simulated long noisy reads</b>	<b>33</b>
<b>13</b>	<b>Performance comparison between NextPolish and Pilon using actual biological data</b>	<b>37</b>
<b>14</b>	<b>NextPolish</b>	<b>43</b>
14.1	Installation . . . . .	43
14.2	Quick Start . . . . .	44
14.3	Getting Help . . . . .	45
14.4	Copyright . . . . .	45
14.5	Cite . . . . .	45
14.6	Limitations . . . . .	45
14.7	Star . . . . .	45
<b>Index</b>		<b>47</b>

NextPolish is used to fix base errors (SNV/Indel) in the genome generated by noisy long reads, it can be used with short read data only or long read data only or a combination of both. It contains two core modules, and use a stepwise fashion to correct the error bases in reference genome. To correct/assemble the raw third-generation sequencing (TGS) long reads with approximately 10-15% sequencing errors, please use [NextDenovo](#).



# CHAPTER 1

---

## Installation

---

- **DOWNLOAD**

click [here](#) or use the following command:

```
wget https://github.com/Nextomics/NextPolish/releases/latest/download/NextPolish.  
→tgz
```

---

**Note:** If you get an error like version 'GLIBC\_2.14' not found or liblzma.so.0: cannot open shared object file, Please download [this version](#).

---

- **REQUIREMENT**

- Python (Support python 2 and 3):

- \* Paralleltask

- **INSTALL**

```
pip install paralleltask  
tar -vxzf NextPolish.tgz && cd NextPolish && make
```

- **UNINSTALL**

```
cd NextPolish && make clean
```

- **TEST**

```
nextPolish test_data/run.cfg
```





## CHAPTER 2

---

### Quick Start

---

#### 1. Prepare sgs\_fofn

```
ls reads1_R1.fq reads1_R2.fq reads2_R1.fq reads2_R2.fq > sgs.fofn
```

#### 2. Create run.cfg

```
genome=input.genome.fa
echo -e "task = best\ngenome = $genome\nsgs_fofn = sgs.fofn" > run.cfg
```

#### 3. Run

```
nextPolish run.cfg
```

#### 4. Finally polished genome

- Sequence: /path\_to\_work\_directory/genome.nextpolish.fasta
- Statistics: /path\_to\_work\_directory/genome.nextpolish.fasta.stat

---

**Tip:** You can also use your own alignment pipeline, and then only use NextPolish to polish the genome, which will be faster than the default pipeline when running on a local system. The accuracy of the polished genome is the same as the default. See following for an example (using bwa to do alignment).

```
#Set input and parameters
round=2
threads=20
read1=reads_R1.fastq.gz
read2=reads_R2.fastq.gz
input=input.genome.fa
for ((i=1; i<=${round};i++)); do
#step 1:
  #index the genome file and do alignment
  bwa index ${input};
  bwa mem -t ${threads} ${input} ${read1} ${read2}|samtools view --threads 3 -F 0x4 -
  ↪b -|samtools fixmate -m --threads 3 - -|samtools sort -m 2g --threads 5 -|samtools
  ↪b -|samtools markdup --threads 5 -r - sgs.sort.bam
```

(continues on next page)

(continued from previous page)

```
#index bam and genome files
samtools index -@ ${threads} sgs.sort.bam;
samtools faidx ${input};
#polish genome file
python NextPolish/lib/nextpolish1.py -g ${input} -t 1 -p ${threads} -s sgs.sort.
↪bam > genome.polishtemp.fa;
  input=genome.polishtemp.fa;
#step2:
  #index genome file and do alignment
  bwa index ${input};
  bwa mem -t ${threads} ${input} ${read1} ${read2}|samtools view --threads 3 -F 0x4 -
↪b -|samtools fixmate -m --threads 3 - -|samtools sort -m 2g --threads 5 -|samtools.
↪markdup --threads 5 -r - sgs.sort.bam
  #index bam and genome files
  samtools index -@ ${threads} sgs.sort.bam;
  samtools faidx ${input};
  #polish genome file
  python NextPolish/lib/nextpolish1.py -g ${input} -t 2 -p ${threads} -s sgs.sort.
↪bam > genome.nextpolish.fa;
  input=genome.nextpolish.fa;
done;
#Finally polished genome file: genome.nextpolish.fa
```

---

**Note:** It is recommend to use long reads to polish the raw genome (set `task` start with “5” and `lgs_fofn` or use `racon`) before polishing with short reads to avoid incorrect mapping of short reads in some high error rate regions, especially for the assembly generated without a consensus step, such as `miniasm`.

---

## CHAPTER 3

---

### Getting Help

---

- **HELP**

Feel free to raise an issue at the [issue page](#). They would also be helpful to other users.

- **CONTACT**

For additional help, please send an email to [huj\\_at\\_grandomics\\_dot\\_com](mailto:huj_at_grandomics_dot_com).



## CHAPTER 4

---

Copyright

---

NextPolish is freely available for academic use and other non-commercial use.



## CHAPTER 5

---

Cite

---

Hu, Jiang, et al. “NextPolish: a fast and efficient genome polishing tool for long read assembly.” Bioinformatics (Oxford, England) (2019).





## CHAPTER 6

---

### Limitations

---

NextPolish is designed for genomes assembled by long reads, so it assumes an input genome without gaps (N bases). Therefore, please split your genome assembly by its gaps and then link them back after polishing if your input contains gaps. Usually we scaffolded a genome using BioNano or Hic data after a polishing step.



## CHAPTER 7

---

Star

---

You can track updates by tab the `Star` button on the upper-right corner at the [github page](#).



- *Polishing using short reads only*
- *Polishing using long reads only*
- *Polishing using short reads and long reads*
- *Polishing using short reads and hifi reads*

## 8.1 Polishing using short reads only

1. Prepare sgs\_fofn

```
ls reads1_R1.fq reads1_R2.fq reads2_R1.fq reads2_R2.fq > sgs.fofn
```

2. Create run.cfg

```
[General]
job_type = local
job_prefix = nextPolish
task = best
rewrite = yes
rerun = 3
parallel_jobs = 6
multithread_jobs = 5
genome = ./raw.genome.fasta #genome file
genome_size = auto
workdir = ./01_rundir
polish_options = -p {multithread_jobs}

[sgs_option]
```

(continues on next page)

(continued from previous page)

```
sgs_fofn = ./sgs.fofn
sgs_options = -max_depth 100 -bwa
```

### 3. Run

```
nextPolish run.cfg
```

### 4. Finally polished genome

- Sequence: /path\_to\_work\_directory/genome.nextpolish.fasta
- Statistics: /path\_to\_work\_directory/genome.nextpolish.fasta.stat

**Tip:** User defined alignment pipeline, which will be faster than the default pipeline when running on a local system. The accuracy of the polished genome is the same as the default.

```
#Set input and parameters
round=2
threads=20
read1=reads_R1.fastq.gz
read2=reads_R2.fastq.gz
input=input.genome.fa
for ((i=1; i<=${round};i++)); do
#step 1:
#index the genome file and do alignment
bwa index ${input};
bwa mem -t ${threads} ${input} ${read1} ${read2}|samtools view --threads 3 -F 0x4 -
↪b -|samtools fixmate -m --threads 3 - -|samtools sort -m 2g --threads 5 -|samtools_
↪markdup --threads 5 -r - sgs.sort.bam
#index bam and genome files
samtools index -@ ${threads} sgs.sort.bam;
samtools faidx ${input};
#polish genome file
python NextPolish/lib/nextpolish1.py -g ${input} -t 1 -p ${threads} -s sgs.sort.
↪bam > genome.polishtemp.fa;
input=genome.polishtemp.fa;
#step2:
#index genome file and do alignment
bwa index ${input};
bwa mem -t ${threads} ${input} ${read1} ${read2}|samtools view --threads 3 -F 0x4 -
↪b -|samtools fixmate -m --threads 3 - -|samtools sort -m 2g --threads 5 -|samtools_
↪markdup --threads 5 -r - sgs.sort.bam
#index bam and genome files
samtools index -@ ${threads} sgs.sort.bam;
samtools faidx ${input};
#polish genome file
python NextPolish/lib/nextpolish1.py -g ${input} -t 2 -p ${threads} -s sgs.sort.
↪bam > genome.nextpolish.fa;
input=genome.nextpolish.fa;
done;
#Finally polished genome file: genome.nextpolish.fa
```

## 8.2 Polishing using long reads only

### 1. Prepare lgs\_fofn

```
ls reads1.fq reads2.fa.gz > lgs.fofn
```

### 2. Create run.cfg

```
[General]
job_type = local
job_prefix = nextPolish
task = best
rewrite = yes
rerun = 3
parallel_jobs = 6
multithread_jobs = 5
genome = ./raw.genome.fasta #genome file
genome_size = auto
workdir = ./01_rundir
polish_options = -p {multithread_jobs}

[lgs_option]
lgs_fofn = ./lgs.fofn
lgs_options = -min_read_len 1k -max_depth 100
lgs_minimap2_options = -x map-ont
```

### 3. Run

```
nextPolish run.cfg
```

### 4. Finally polished genome

- Sequence: /path\_to\_work\_directory/genome.nextpolish.fasta
- Statistics: /path\_to\_work\_directory/genome.nextpolish.fasta.stat

**Tip:** User defined alignment pipeline, which will be faster than the default pipeline when running on a local system. The accuracy of the polished genome is the same as the default.

```
#Set input and parameters
round=2
threads=20
read=read.fasta.gz
read_type=ont #{clr,hifi,ont}, clr=PacBio continuous long read, hifi=PacBio highly_
↳accurate long reads, ont=NanoPore 1D reads
mapping_option=(["clr"]="map-pb" ["hifi"]="asm20" ["ont"]="map-ont")
input=input.genome.fa

for ((i=1; i<=${round};i++)); do
    minimap2 -ax ${mapping_option[$read_type]} -t ${threads} ${input} ${read}
    ↳|samtools sort - -m 2g --threads ${threads} -o lgs.sort.bam;
    samtools index lgs.sort.bam;
    ls `pwd`/lgs.sort.bam > lgs.sort.bam.fofn;
    python NextPolish/lib/nextpolish2.py -g ${input} -l lgs.sort.bam.fofn -r ${read_
    ↳type} -p ${threads} -sp -o genome.nextpolish.fasta;
    if ((i!=${round}));then
        mv genome.nextpolish.fasta genome.nextpolishtmp.fasta;
```

(continues on next page)

```
    input=genome.nextpolishtmp.fa;
fi;
done;
# Finally polished genome file: genome.nextpolish.fa
```

## 8.3 Polishing using short reads and long reads

### 1. Prepare sgs\_fofn

```
ls reads1_R1.fq reads1_R2.fq reads2_R1.fq reads2_R2.fq > sgs.fofn
```

### 2. Prepare lgs\_fofn

```
ls reads1.fq reads2.fa.gz > lgs.fofn
```

### 3. Create run.cfg

```
[General]
job_type = local
job_prefix = nextPolish
task = best
rewrite = yes
rerun = 3
parallel_jobs = 6
multithread_jobs = 5
genome = ./raw.genome.fasta
genome_size = auto
workdir = ./01_rundir
polish_options = -p {multithread_jobs}

[sgs_option]
sgs_fofn = ./sgs.fofn
sgs_options = -max_depth 100 -bwa

[lgs_option]
lgs_fofn = ./lgs.fofn
lgs_options = -min_read_len 1k -max_depth 100
lgs_minimap2_options = -x map-ont
```

### 4. Run

```
nextPolish run.cfg
```

### 5. Finally polished genome

- Sequence: /path\_to\_work\_directory/genome.nextpolish.fasta
- Statistics: /path\_to\_work\_directory/genome.nextpolish.fasta.stat

## 8.4 Polishing using short reads and hifi reads

### 1. Prepare sgs\_fofn



```
ls reads1_R1.fq reads1_R2.fq reads2_R1.fq reads2_R2.fq > sgs.fofn
```

## 2. Prepare hifi\_fofn

```
ls reads1.fq reads2.fa.gz > hifi.fofn
```

## 3. Create run.cfg

```
[General]
job_type = local
job_prefix = nextPolish
task = best
rewrite = yes
rerun = 3
parallel_jobs = 6
multithread_jobs = 5
genome = ./raw.genome.fasta
genome_size = auto
workdir = ./01_rundir
polish_options = -p {multithread_jobs}

[sgs_option]
sgs_fofn = ./sgs.fofn
sgs_options = -max_depth 100 -bwa

[hifi_option]
hifi_fofn = ./hifi.fofn
hifi_options = -min_read_len 1k -max_depth 100
hifi_minimap2_options = -x map-pb
```

## 4. Run

```
nextPolish run.cfg
```

## 5. Finally polished genome

- Sequence: /path\_to\_work\_directory/genome.nextpolish.fasta
- Statistics: /path\_to\_work\_directory/genome.nextpolish.fasta.stat



---

## NextPolish Parameter Reference

---

NextPolish requires at least one assembly file (option: `genome`) and one read file list (option: `sgs_fofn` or `lgs_fofn` or `hifi_fofn`) as input, it works with gzip'd FASTA and FASTQ formats and uses a config file to pass options.

### 9.1 Input

- genome file

```
genome=/path/to/need_to_be_polished_assembly_file
```

- read file list (one file one line, paired-end files should be interleaved)

```
ls reads1_R1.fq reads1_R2.fq reads2_R1.fq.gz reads2_R2.fq.gz ... > sgs.fofn
```

- config file

A config file is a text file that contains a set of parameters (key=value pairs) to set runtime parameters for NextPolish. The following is a typical config file, which is also located in `doc/run.cfg`.

```
[General]
job_type = local
job_prefix = nextPolish
task = best
rewrite = yes
deltmp = yes
rerun = 3
parallel_jobs = 6
multithread_jobs = 5
genome = ./raw.genome.fasta
genome_size = auto
workdir = ./01_rundir
polish_options = -p {multithread_jobs}
```

(continues on next page)

```
[sgs_option] #optional
sgs_fofn = ./sgs.fofn
sgs_options = -max_depth 100 -bwa

[lgs_option] #optional
lgs_fofn = ./lgs.fofn
lgs_options = -min_read_len 1k -max_depth 100
lgs_minimap2_options = -x map-ont

[hifi_option] #optional
hifi_fofn = ./hifi.fofn
hifi_options = -min_read_len 1k -max_depth 100
hifi_minimap2_options = -x asm20
```

## 9.2 Output

- `genome.nextpolish.fasta`  
Polished genome with fasta format, the fasta header includes primary seqID, length. A lowercase letter indicates a low quality base after polishing, this usually caused by heterozygosity.
- `genome.nextpolish.fasta.stat`  
Some basic statistical information of the polished genome.

## 9.3 Options

### 9.3.1 Global options

```
job_type = sge
    local, sge, pbs... (default: sge)

job_prefix = nextPolish
    prefix tag for jobs. (default: nextPolish)

task = best
    task need to run [all, default, best, 1, 2, 5, 12, 1212...], 1, 2 are different algorithm modules for short reads, while 5 is the algorithm module for long reads, all=[5]1234, default=[5]12, best=[55]1212. (default: best)

rewrite = no
    overwrite existed directory [yes, no]. (default: no)

deltmp = yes
    delete intermediate results. (default: yes)

rerun = 3
    re-run unfinished jobs until finished or reached ${rerun} loops, 0=no. (default: 3)

parallel_jobs = 6
    number of tasks used to run in parallel. (default: 6)

multithread_jobs = 5
    number of threads used to in a task. (default: 5)
```

```

submit = auto
    command to submit a job, auto = automatically set by Paralleltask.

kill = auto
    command to kill a job, auto = automatically set by Paralleltask.

check_alive = auto
    command to check a job status, auto = automatically set by Paralleltask.

job_id_regex = auto
    the job-id-regex to parse the job id from the out of submit, auto = automatically set by Paralleltask.

use_drmaa = no
    use drmaa to submit and control jobs.

genome = genome.fa
    genome file need to be polished. (required)

genome_size = auto
    genome size, auto = calculate genome size using the input {genome} file. (default: auto)

workdir = 01_rundir
    work directory. (default: ./)

polish_options = -p {multithread_jobs}

```

```

-p, number of processes used for polishing.
-u, output uppercase sequences. (default: False)
-debug, output details of polished bases to stderr, only useful in short_  

↳read polishing. (default: False)

```

### 9.3.2 Options for short reads

```

sgs_fofn = ./sgs.fofn
    input short read files list, one file one line, paired-end files should be interleaved.

sgs_options = -max_depth 100 -bwa

```

```

-N, don't discard a read/pair if the read contains N base.
-use_duplicate_reads, use duplicate pair-end reads in the analysis.  

↳(default: False)
-unpaired, unpaired input files. (default: False)
-max_depth, use up to {max_depth} fold reads data to polish. (default:  

↳100)
-bwa, use bwa to do mapping. (default: -bwa)
-minimap2, use minimap2 to do mapping, which is much faster than bwa.

```

### 9.3.3 Options for long reads

```

lgs_fofn = ./lgs.fofn
    input long read files list, one file one line.

lgs_options = -min_read_len 1k -max_depth 100

```

```
-min_read_len, filter reads with length shorter than ${min_read_len}.  
↳ (default: 1k)  
-max_read_len, filter reads with length longer than $ {max_read_len},  
↳ ultra-long reads usually contain lots of errors, and the mapping step  
↳ requires significantly more memory and time, 0=disable (default: 0)  
-max_depth, use up to ${max_depth} fold reads data to polish, 0=disable.  
↳ (default: 100)
```

**lgs\_minimap2\_options** = -x map-pb -t {multithread\_jobs}  
minimap2 options, used to set PacBio/Nanopore reads mapping. **(required)**

### 9.3.4 Options for hifi reads

**hifi\_fofn** = ./hifi.fofn  
input hifi read files list, one file one line.

**hifi\_options** = -min\_read\_len 1k -max\_depth 100

```
-min_read_len, filter reads with length shorter than ${min_read_len}.  
↳ (default: 1k)  
-max_read_len, filter reads with length longer than $ {max_read_len},  
↳ ultra-long reads usually contain lots of errors, and the mapping step  
↳ requires significantly more memory and time, 0=disable (default: 0)  
-max_depth, use up to ${max_depth} fold reads data to polish, 0=disable.  
↳ (default: 100)
```

**hifi\_minimap2\_options** = -x map-pb -t {multithread\_jobs}  
minimap2 options, used to set hifi reads mapping. **(required)**

---

## Frequently Asked Questions

---

- *What is the difference between NextPolish and Pilon?*
- *Which job scheduling systems are supported by NextPolish?*
- *How to continue running unfinished tasks?*
- *How to set the task parameter?*
- *How many iterations to run NextPolish cyclically to get the best result?*
- *Why does the contig N50 of polished genome become shorter or why does the polished genome contains some extra N?*
- *What is the difference between bwa or minimap2 to do SGS data mapping?*
- *How to specify the queue/cpu/memory/bash to submit jobs?*

### 10.1 What is the difference between NextPolish and Pilon?

Currently, NextPolish is focuses on genome correction using shotgun reads, which is also one of the most important steps (typically the last step) to accomplish a genome assembly, while Pilon can be used to make other improvements. For genome correction, NextPolish consumes considerable less time and has a higher correction accuracy for genomes with same sizes and such an advantage becomes more and more significant when the genome size of targeted assemblies increased compared to Pilon. See BENCHMARK section for more details.

### 10.2 Which job scheduling systems are supported by NextPolish?

NextPolish use `Paralleltask` to submit, control, and monitor jobs, so in theory, support all `Paralleltask`-compliant system, such as LOCAL, SGE, PBS, SLURM.

## 10.3 How to continue running unfinished tasks?

No need to make any changes, simply run the same command again.

## 10.4 How to set the *task* parameter?

The `task` parameter is used to set the polishing algorithm logic, 1, 2, 3, 4 are different algorithm modules for short reads, while 5 is the algorithm module for long reads. BTW, steps 3 and 4 are experimental, and we do not currently recommend running on a actual project. Set `task=551212` means NextPolish will cyclically run steps 5, 1 and 2 with 2 iterations.

## 10.5 How many iterations to run NextPolish cyclically to get the best result?

Our test shown that run NextPolish with 2 iterations, and most of the bases with effectively covered by SGS data can be corrected. Please set `task=best` to get the best result. `task = best` means NextPolish will cyclically run steps [5], 1 and 2 with 2 iterations. Of course, you can require NextPolish to run with more iterations to get a better result, such as set `task=555512121212`, which means NextPolish will cyclically run steps 5, 1 and 2 with 4 iterations.

## 10.6 Why does the contig N50 of polished genome become shorter or why does the polished genome contains some extra N?

In some cases, if the short reads contain N, some error bases will be fixed by N (the global score of a kmer with N is the largest and be selected), and remove N in short reads will avoid this.

## 10.7 What is the difference between bwa or minimap2 to do SGS data mapping?

Our test shown Minimap2 is about 3 times faster than bwa, but the accuracy of polished genomes using minimap2 or bwa is tricky, depending on the error rate of genomes and SGS data, see [here](#) for more details.

## 10.8 How to specify the queue/cpu/memory/bash to submit jobs?

See [here](#) to edit the `Paralleltask` configure template file `cluster.cfg`, or use the `submit` parameter.



---

## Performance comparison between NextPolish, Pilon and Racon using simulated short reads

---

### REQUIREMENT

- ART v2.5.8
- PBSIM v1.0.4
- CANU v1.8
- Pilon v1.23
- Racon v1.3.3
- NextPolish v1.0.3
- Quast v5.0.2

#### 1. Download reference

```
curl -SL ftp://ftp.ensembl.org/pub/release-96/fasta/homo_sapiens/dna/Homo_
↳sapiens.GRCh38.dna.chromosome.1.fa.gz | gunzip - > chr01.fa
```

#### 2. Simulate PacBio data

```
pbsim --data-type CLR --model_gc /PBSIM-PacBio-Simulator/data/model_gc_clr --
↳depth 50 --length-mean 10000 --accuracy-mean 0.85 --prefix pacbio chr01.fa
```

#### 3. Simulate Illumina data

```
art_illumina -ss HS25 -i chr01.fa -p -l 150 -f 50 -m 300 -s 10 -o NGS_
```

#### 4. Assemble reference

```
canu -pacbio-raw pacbio_0001.fastq -p asm -d canu-pb useGrid=True_
↳genomeSize=250m gridEngineMemoryOption="-l vf=MEMORY"
```

#### 5. Run Pilon

- work.sh

```
genome=asm.contigs.fasta
reads1=NGS_1.fq
reads2=NGS_1.fq
input=${genome}
for i in {1..4};do
    NextPolish/bin/bwa index ${input};
    NextPolish/bin/bwa mem -t 25 ${input} ${reads1} ${reads2} |NextPolish/
↪bin/samtools view -b - |NextPolish/bin/samtools fixmate -m --threads 5 - -
↪ |NextPolish/bin/samtools sort -m 5g --threads 5 - -o ${input}.sort.bam;
    NextPolish/bin/samtools index ${input}.sort.bam;
    time -p java -Xmx50G -jar /home/huj/software/pilon-1.23.jar --genome $
↪{input} --frags ${input}.sort.bam --output ${genome}.pilon.v${i} --
↪threads 5 --fix bases;
    input=${genome}.pilon.v${i}.fasta;
done
```

- Run

```
nohup sh work.sh > pilon.log &
```

- CPU time used for polishing

```
egrep 'user|sys' pilon.log|awk '{x+=$2}END{print x}'
```

## 6. Run Racon

- work.sh

```
awk '{if (NR%4==1){print $0"1"}else{print $0}}' NGS_1.fq > NGS_1.rn.fq;
awk '{if (NR%4==1){print $0"1"}else{print $0}}' NGS_2.fq > NGS_2.rn.fq;
cat NGS_1.rn.fq NGS_2.rn.fq > NGS.rn.fq;
genome=asm.contigs.fasta
reads1=NGS_1.rn.fq
reads2=NGS_2.rn.fq
input=${genome}
for i in {1..4};do
    NextPolish/bin/minimap2 -ax sr ${input} ${reads1} ${reads2} > input.sam
    time -p racon NGS.rn.fq input.sam ${input} --include-unpolished --
↪threads 5 > ${genome}.racon.v${i}.fasta;
    input=${genome}.racon.v${i}.fasta;
done
```

- Run

```
nohup sh work.sh > racon.log &
```

- CPU time used for polishing

```
egrep 'user|sys' racon.log|awk '{x+=$2}END{print x}'
```

## 7. Run NextPolish

- run.cfg

```
[General]
job_type = local
```

(continues on next page)

(continued from previous page)

```

job_prefix = nextPolish
task = 1212
rewrite = yes
rerun = 3
parallel_jobs = 1
multithread_jobs = 5
genome = asm.contigs.fasta
genome_size = auto
workdir = ./01_rundir
polish_options = -p {multithread_jobs}

[sgs_option]
sgs_fofn = sgs.fofn
sgs_options = -max_depth 100 -bwa

```

- Run

```

ls NGS_1.fq NGS_2.fq > sgs.fofn
nextPolish run.cfg

```

- CPU time used for polishing

```

egrep 'user|sys' 01_rundir/*/*0*.polish.ref.sh.work/polish_genome*/nextPolish.
↪sh.e|awk '{print $2}'|sed 's/m/\t/' |sed 's/s//' |awk '{x+=$1*60+$2}END
↪{print x}'

```

## 8. Run Quast

- Input
- Pilon x 1: asm.contigs.pilonv1.fasta
- Pilon x 2: asm.contigs.pilonv2.fasta
- Pilon x 3: asm.contigs.pilonv3.fasta
- Pilon x 4: asm.contigs.pilonv4.fasta
- Racon x 1: asm.contigs.raconv1.fasta
- Racon x 2: asm.contigs.raconv2.fasta
- Racon x 3: asm.contigs.raconv3.fasta
- Racon x 4: asm.contigs.raconv4.fasta
- NextPolish x 1:

```

cat 01_rundir/01.kmer_count/**.polish.ref.sh.work/polish_genome*/genome.
↪nextpolish.part*.fasta > asm.contigs.nextpolishv1.fasta

```

- NextPolish x 2:

```

cat 01_rundir/03.kmer_count/*mar.polish.ref.sh.work/polish_genome*/
↪genome.nextpolish.part*.fasta > asm.contigs.nextpolishv2.fasta

```

- Run

```

quast/quast-5.0.2/quast.py -e --min-contig 1000000 --min-alignment 50000 --
↪extensive-mis-size 7000 -r chr01.fa asm.contigs.fasta asm.contigs.
↪nextpolishv1.fasta asm.contigs.nextpolishv2.fasta asm.contigs.pilonv1.
↪fasta asm.contigs.pilonv2.fasta asm.contigs.pilonv3.fasta asm.contigs.
↪pilonv4.fasta asm.contigs.raconv1.fasta asm.contigs.raconv2.fasta asm.
↪contigs.raconv3.fasta asm.contigs.raconv4.fasta

```

(continues on next page)

(continued from previous page)

**Quast result**

	asmcast	cas	con	gms	on	gms	next	gms	polish	next	gms	polish	2	asm	cas	con	gms	polish	3	asm	cas	con	gms	polish	3	raconv4	
Total length (>= 0 bp)	22478032	22471636	21522415	215223160	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152	215223152
Reference length	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422	248956422
Unaligned length	56553	61272	61269	62646	61699	61703	61275	163683	177973	176917	193791																
Largest alignment	3868488	3865714	3865713	38657017	3865698	3865703	3865703	3855450	3853700	3853551	38523009																
# mismatches per 100 kbp	17.82	2.38	2.26	2.92	2.39	2.31	2.31	3.08	2.91	2.87	2.64																
# indels per 100 kbp	121.45	0.81	0.71	1.60	1.36	1.28	1.25	1.97	1.16	1.08	1.00																
# mismatches	38286	5107	4863	6275	5134	4974	4957	6625	6249	6177	5684																
# indels	26101	11736	1527	3447	2917	2754	2684	4242	2494	2312	2148																

**Note:** The complete result of Quast can be seen from [here](#).

---

## Performance comparison between NextPolish and Racon using simulated long noisy reads

---

### REQUIREMENT

- PBSIM v1.0.4
- NanoSim v2.6.0
- minimap2 v2.15-r915-dirty
- miniasm v0.3-r179
- gfatools v0.4-r179-dirty
- samtools v1.9
- Racon v1.3.3
- NextPolish v1.2.2
- Quast v5.0.2

#### 1. Download reference

```
curl -SL ftp://ftp.ensembl.org/pub/release-96/fasta/homo_sapiens/dna/Homo_
↪sapiens.GRCh38.dna.chromosome.1.fa.gz | gunzip - > chr01.fa
```

#### 2. Simulate PacBio data

```
pbsim --data-type CLR --model_qc /PBSIM-PacBio-Simulator/data/model_qc_clr --
↪depth 50 --length-mean 10000 --accuracy-mean 0.85 --prefix pacbio chr01.fa
```

#### 3. Simulate NanoPore data

```
python NanoSim/src/simulator.py genome -rg chr01.fa -c NanoSim/pre-trained_
↪models/human_NA12878_DNA_FAB49712_guppy/training -n 1631727 -b guppy
cat simulated_aligned_reads.fasta simulated_unaligned_reads.fasta > ont.
↪sumulated.reads.fa
```

### 4. Assemble reference

- PacBio data

```
minimap2 -t 30 -x ava-pb pb.sumulated.reads.fa pb.sumulated.reads.fa > pb.  
↪asm.paf  
miniasm -f pb.sumulated.reads.fa pb.asm.paf > pb.asm.gfa  
gfatools gfa2fa pb.asm.gfa > pb.asm.fa
```

- NanoPore data

```
minimap2 -t 30 -x ava-ont ont.sumulated.reads.fa ont.sumulated.reads.fa >  
↪ont.asm.paf  
miniasm -f ont.sumulated.reads.fa ont.asm.paf > ont.asm.gfa  
gfatools gfa2fa ont.asm.gfa > ont.asm.fa
```

### 5. Run Racon

- PacBio data

```
minimap2 -x map-pb -t 20 pb.asm.fa pb.sumulated.reads.fa > pb.map.paf  
racon -t 20 pb.sumulated.reads.fa pb.map.paf pb.asm.fa > pb.asm.racon1.fa
```

- NanoPore data

```
minimap2 -x map-ont -t 20 ont.asm.fa ont.sumulated.reads.fa > ont.map.paf  
racon -t 20 ont.sumulated.reads.fa ont.map.paf ont.asm.fa > ont.asm.racon1.fa
```

### 6. Run NextPolish

- PacBio data

```
minimap2 -ax map-pb -t 20 pb.asm.fa pb.sumulated.reads.fa|samtools sort - -m  
↪2g --threads 20 -o pb.map.bam  
samtools index pb.map.bam  
ls `pwd`/pb.map.bam > pb.map.bam.fofn  
python NextPolish/lib/nextpolish2.py -g pb.asm.fa -l pb.map.bam.fofn -r clr -  
↪p 20 -sp -o pb.asm.nextpolish1.fa
```

- NanoPore data

```
minimap2 -ax map-ont -t 20 ont.asm.fa ont.sumulated.reads.fa|samtools sort -  
↪-m 2g --threads 20 -o ont.map.bam  
samtools index ont.map.bam  
ls `pwd`/ont.map.bam > ont.map.bam.fofn  
python NextPolish/lib/nextpolish2.py -g ont.asm.fa -l ont.map.bam.fofn -r  
↪ont -p 20 -sp -o ont.asm.nextpolish1.fa
```

---

**Note:** Here we use a custom alignment pipeline and then use NextPolish to polish the genome. The genome accuracy after polishing is the same as using NextPolish pipeline to do alignment, see [Tutorial](#).

---

### 7. Run Quast

- Input

- PacBio data

- \* pb.asm.fa

```
* pb.asm.nextpolish1.fa
```

```
* pb.asm.racon1.fa
```

– NanoPore data

```
* ont.asm.fa
```

```
* ont.asm.nextpolish1.fa
```

```
* ont.asm.racon1.fa
```

• Run

```
quast.py --eukaryote --large --threads 25 --min-identity 85 -r chr01.fa pb.
↪asm.fa pb.asm.nextpolish1.fa pb.asm.racon1.fa ont.asm.fa ont.asm.
↪nextpolish1.fa ont.asm.racon1.fa
```

**Quast result**

	pb.asm	pb.asm.nextpolish1	pb.asm.racon1	ont.asm	ont.asm.nextpolish1	ont.asm.racon1
Total length (>= 0 bp)	23889388	229392481	231583305	22173950	231851442	231932961
Reference length	24895642	248956422	248956422	24895642	248956422	248956422
Unaligned length	1002739	307941	70526	6235359	6163688	6431927
Largest alignment	2658861	225515573	25771470	30803348	32268337	32271759
# mismatches per 100 kbp	5425.25	165.25	115.42	4973.49	30.79	34.63
# indels per 100 kbp	7127.93	631.97	1233.12	4126.88	43.39	83.87
# mismatches	12141134	370583	258809	11129037	68890	77504
# indels	15951531	1417256	2765093	9234603	97088	187713

**Note:** The complete result of Quast can be seen from [here](#).





---

## Performance comparison between NextPolish and Pilon using actual biological data

---

### REQUIREMENT

- Miniasm v0.2
- Falcon v1.8.7
- Pilon v1.23
- Racon v1.3.3
- NextPolish v1.0.3
- Seqkit v0.10.1
- Gmap v2017-01-14
- Freebayes v1.2.0-10

#### 1. Download data

- Sequencing data
- *Arabidopsis thaliana*
- *Homo sapiens*
- Genes
- *Arabidopsis thaliana*
- *Homo sapiens*

#### 2. Assembly

- *Arabidopsis thaliana*
  - PacBio data

```
minimap2 -x ava-pb pb.reads.fq pb.reads.fq | gzip -1 > overlaps.paf.gz
miniasm -f pb.reads.fq overlaps.paf.gz > miniasm.gfa
awk '{if($1=="S"){print ">"$2;print $3}}' miniasm.gfa > miniasm.fasta
```

### - NanoPore data

```
minimap2 -x ava-ont ont.reads.fq ont.reads.fq | gzip -1 > overlaps.paf.gz
miniasm -f ont.reads.fq overlaps.paf.gz > miniasm.gfa
awk '{if($1=="S"){print ">"$2;print $3}}' miniasm.gfa > miniasm.fasta
```

### • *Homo sapiens*

#### - fc\_run.cfg

```
job_type = sge
input_fofn = input.fofn
input_type = raw

length_cutoff = 11000
length_cutoff_pr = 12000

stop_all_jobs_on_failure = False
target = assembly

job_queue = all.q
sge_option_da = -pe smp 4 -q %(job_queue)s
sge_option_la = -pe smp 4 -q %(job_queue)s
sge_option_pda = -pe smp 4 -q %(job_queue)s
sge_option_pla = -pe smp 4 -q %(job_queue)s
sge_option_fc = -pe smp 10 -q %(job_queue)s
sge_option_cns = -pe smp 4 -q %(job_queue)s

pa_concurrent_jobs = 499
ovlp_concurrent_jobs = 499
cns_concurrent_jobs = 499

pa_HPCdaligner_option = -v -B256 -t12 -w8 -e0.75 -k18 -h260 -l2000 -s1000 -T4
ovlp_HPCdaligner_option = -v -B128 -t12 -k20 -h360 -e.96 -l1800 -s1000 -T4

pa_DBsplit_option = -x1000 -s200 -a
ovlp_DBsplit_option = -x1000 -s200

falcon_sense_option = --output_multi --min_idt 0.75 --min_cov 4 --max_n_read 200_
↪--n_core 4
overlap_filtering_setting = --max_diff 70 --max_cov 100 --min_cov 2 --bestn 10 --
↪n_core 10
```

#### - Run

```
fc_run.py fc_run.cfg
```

### 3. Run Racon

- *Arabidopsis thaliana*
  - PacBio data

```

genome=miniasm.fasta
reads=pb.reads.fq
input=${genome}
for i in {1..4};do
    minimap2 -x map-pb ${input} ${reads} > align.paf;
    racon -t 10 ${reads} align.paf ${input} > ${genome}.racon.v${i}.
↪fasta;
    input=${genome}.racon.v${i}.fasta;
done;

```

- NanoPore data

```

genome=miniasm.fasta
reads=ont.reads.fq
input=${genome}
for i in {1..4};do
    minimap2 -x map-ont ${input} ${reads} > align.paf;
    racon -t 10 ${reads} align.paf ${input} > ${genome}.racon.v${i}.
↪fasta;
    input=${genome}.racon.v${i}.fasta;
done;

```

#### 4. Run Pilon

- *Arabidopsis thaliana*

- work.sh

```

genome=miniasm.racon.v4.fasta
reads1=NGS_1.fq
reads2=NGS_1.fq
input=${genome}
for i in {1..4};do
    NextPolish/bin/bwa index ${input};
    NextPolish/bin/bwa mem -t 25 ${input} ${reads1} ${reads2}
↪|NextPolish/bin/samtools view -b - |NextPolish/bin/samtools
↪fixmate -m --threads 5 - - |NextPolish/bin/samtools sort -m 5g --
↪threads 5 - -o ${input}.sort.bam;
    NextPolish/bin/samtools index ${input}.sort.bam;
    time -p java -Xmx50G -jar /home/huj/software/pilon-1.23.jar --
↪genome ${input} --frags ${input}.sort.bam --output ${genome}.pilon.
↪v${i} --threads 5 --fix bases;
    input=${genome}.pilon.v${i}.fasta;
done

```

- *Homo sapiens*

- work.sh

```

genome=p_ctg.fa
reads1=NGS_1.fq
reads2=NGS_1.fq
input=${genome}
for i in {1..4};do
    NextPolish/bin/bwa index ${input};
    NextPolish/bin/bwa mem -t 25 ${input} ${reads1} ${reads2}
↪|NextPolish/bin/samtools view -b - |NextPolish/bin/samtools
↪fixmate -m --threads 5 - - |NextPolish/bin/samtools sort -m 5g --
↪threads 5 - -o ${input}.sort.bam;

```

(continues on next page)

(continued from previous page)

```

NextPolish/bin/samtools index ${input}.sort.bam;
seqkit split2 -p 20 ${input};
ls ${input}.split|while read line;do time -p java -Xmx120G -jar /
↪home/huj/software/pilon-1.23.jar --genome ${line} --frags ${input}.
↪sort.bam --output ${line}.pilon --threads 5 --fix bases;done;
cat ${input}.split/*.pilon.fasta > ${genome}.pilon.v${i}.fasta;
input=${genome}.pilon.v${i}.fasta;
done

```

- Run

```
nohup sh work.sh > pilon.log &
```

- CPU time used for polishing

```
egrep 'user|sys' pilon.log|awk '{x+=$2}END{print x}'
```

## 5. Run NextPolish

- run.cfg

```

[General]
job_type = local
job_prefix = nextPolish
task = 1212
rewrite = yes
rerun = 3
parallel_jobs = 5
multithread_jobs = 5
genome = p_ctg.fa #miniasm.racon.v4.fasta
genome_size = auto
workdir = ./01_rundir
polish_options = -p {multithread_jobs}

[sgs_option]
sgs_fofn = sgs.fofn
sgs_options = -max_depth 100 -bwa

```

- Run

```
ls NGS_1.fq NGS_2.fq > sgs.fofn
nextPolish run.cfg
```

- CPU time used for polishing

```

egrep 'user|sys' 01_rundir/ */0*.polish.ref.sh.work/polish_genome */
↪nextPolish.sh.e|awk '{print $2}'|sed 's/m//'|sed 's/s//'|awk '{x+=$1* 60+
↪$2}END{print x}'

```

## 6. Run Gmap

```

genome=miniasm.racon.v4.pilon.v4.fasta # p_ctg.pilon.v4.fasta
gmap_build -d ./${genome}.gmap ${genome}
gmap -D ./ -d ${genome}.gmap Homo_sapiens.GRCh38.cds.all.filter.fa -F -n 1 -
↪i 0 -t 10 -A > ${genome}.gmap.blast

```

## 7. Run Freebayes

```

genome=miniasm.racon.v4.pilon.v4.fasta # p_ctg.pilon.v4.fasta
reads1=NGS_1.fq
reads2=NGS_1.fq
NextPolish/bin/bwa index ${genome};
NextPolish/bin/bwa mem -t 10 ${genome} ${reads1} ${reads2}|NextPolish/bin/
↪samtools view -b - |NextPolish/bin/samtools sort -m 5g --threads 5 - -o $
↪${genome}.bwa.sort.bam;
NextPolish/bin/samtools index -@ 10 ${genome}.bwa.sort.bam
freebayes -p 2 -b ${genome}.bwa.sort.bam -v ${genome}.sort.bam.vcf -f $
↪${genome}

```

## 8. Count mapped reads

```

#!/usr/bin/env python

import sys
import pysam

bam_file = sys.argv[1]
mapped = full_length_mapped = 0
for i in pysam.AlignmentFile(bam_file, "r"):
    if i.is_unmapped or i.is_supplementary or i.is_secondary:
        continue
    qseq = i.query_sequence.upper()
    rseq = i.get_reference_sequence().upper()
    mapped += 1
    if qseq == rseq:
        full_length_mapped += 1

print 'mapped: %d full_length_mapped: %d' % (mapped, full_length_mapped)

```

## 9. Count SNP/Indel

```

#!/bin/bash

vcf=$1
homosnp=$(grep -v '#' ${vcf}|grep snp|grep "1/1"|wc -l)
echo homosnp: $homosnp

homoindel=$(grep -v '#' ${vcf}|egrep 'ins|del'|grep "1/1"|wc -l)
echo homoindel: $homoindel

hetererrors=$(grep -v '#' ${vcf}|cut -f 10 |sed 's:/\t/g' |awk '$4==0'|grep_
↪-v 1/1 |wc -l)
echo hetererrors: $hetererrors

```

## 10. Count mapped genes

```

#!/usr/bin/env python

import sys

gmap_result_file = sys.argv[1]
total_gene_count = int(sys.argv[2])
maps = unmaps = truncate_maps = 0

names = []

```

(continues on next page)

(continued from previous page)

```
name = cov = aa = qlen = ''
with open(gmap_result_file) as IN:
    for line in IN:
        line = line.strip()
        if not line:
            continue
        lines = line.strip().split()
        if line.startswith('>'):
            if qlen:
                if int(aa) < int(qlen) * 0.95:
                    truncate_maps += 1
                qlen = ''
            elif name in names:
                names.remove(name)

            name = line[1:]
            if name in names:
                print >>sys.stderr, 'duplicate name: ' + name
                sys.exit(1)
            else:
                names.append(name)
        elif line.startswith('Coverage'):
            qlen = str(int(lines[-2])/3)
        elif line.startswith('Translation'):
            aa = lines[-2][1:]

if qlen:
    if int(aa) < int(qlen) * 0.95:
        truncate_maps += 1
elif name in names:
    names.remove(name)

maps = len(names)
unmaps = total_gene_count - maps

print "\t".join(['#', 'unmap', 'truncate_map'])
print "\t".join(map(str, ('#', unmaps, truncate_maps)))
```

11. **Result can be seen from NextPolish paper.**

NextPolish is used to fix base errors (SNV/Indel) in the genome generated by noisy long reads, it can be used with short read data only or long read data only or a combination of both. It contains two core modules, and use a stepwise fashion to correct the error bases in reference genome. To correct/assemble the raw third-generation sequencing (TGS) long reads with approximately 10-15% sequencing errors, please use [NextDenovo](#).

## 14.1 Installation

- **DOWNLOAD**

click [here](#) or use the following command:

```
wget https://github.com/Nextomics/NextPolish/releases/latest/download/NextPolish.  
↪.tgz
```

---

**Note:** If you get an error like version 'GLIBC\_2.14' not found or liblzma.so.0: cannot open shared object file, Please download [this version](#).

---

- **REQUIREMENT**

- Python (Support python 2 and 3):

- \* [Paralleltask](#)

- **INSTALL**

```
pip install paralleltask  
tar -vzxf NextPolish.tgz && cd NextPolish && make
```

- **UNINSTALL**

```
cd NextPolish && make clean
```

- TEST

```
nextPolish test_data/run.cfg
```

## 14.2 Quick Start

### 1. Prepare sgs\_fofn

```
ls reads1_R1.fq reads1_R2.fq reads2_R1.fq reads2_R2.fq > sgs.fofn
```

### 2. Create run.cfg

```
genome=input.genome.fa
echo -e "task = best\ngenome = $genome\nsgs_fofn = sgs.fofn" > run.cfg
```

### 3. Run

```
nextPolish run.cfg
```

### 4. Finally polished genome

- Sequence: /path\_to\_work\_directory/genome.nextpolish.fasta
- Statistics: /path\_to\_work\_directory/genome.nextpolish.fasta.stat

**Tip:** You can also use your own alignment pipeline, and then only use NextPolish to polish the genome, which will be faster than the default pipeline when running on a local system. The accuracy of the polished genome is the same as the default. See following for an example (using bwa to do alignment).

```
#Set input and parameters
round=2
threads=20
read1=reads_R1.fastq.gz
read2=reads_R2.fastq.gz
input=input.genome.fa
for ((i=1; i<=${round};i++)); do
#step 1:
  #index the genome file and do alignment
  bwa index ${input};
  bwa mem -t ${threads} ${input} ${read1} ${read2}|samtools view --threads 3 -F 0x4 -
↪b -|samtools fixmate -m --threads 3 - -|samtools sort -m 2g --threads 5 -|samtools_
↪markdup --threads 5 -r - sgs.sort.bam
  #index bam and genome files
  samtools index -@ ${threads} sgs.sort.bam;
  samtools faidx ${input};
  #polish genome file
  python NextPolish/lib/nextpolish1.py -g ${input} -t 1 -p ${threads} -s sgs.sort.
↪bam > genome.polishtemp.fa;
  input=genome.polishtemp.fa;
#step2:
  #index genome file and do alignment
  bwa index ${input};
  bwa mem -t ${threads} ${input} ${read1} ${read2}|samtools view --threads 3 -F 0x4 -
↪b -|samtools fixmate -m --threads 3 - -|samtools sort -m 2g --threads 5 -|samtools_
↪markdup --threads 5 -r - sgs.sort.bam
```

(continues on next page)



(continued from previous page)

```
#index bam and genome files
samtools index -@ ${threads} sgs.sort.bam;
samtools faidx ${input};
#polish genome file
python NextPolish/lib/nextpolish1.py -g ${input} -t 2 -p ${threads} -s sgs.sort.
↪bam > genome.nextpolish.fa;
input=genome.nextpolish.fa;
done;
#Finally polished genome file: genome.nextpolish.fa
```

**Note:** It is recommend to use long reads to polish the raw genome (set `task` start with “5” and `lgs_fofn` or use `racon`) before polishing with short reads to avoid incorrect mapping of short reads in some high error rate regions, especially for the assembly generated without a consensus step, such as [miniasm](#).

## 14.3 Getting Help

- **HELP**

Feel free to raise an issue at the [issue page](#). They would also be helpful to other users.

- **CONTACT**

For additional help, please send an email to [huj\\_at\\_grandomics\\_dot\\_com](mailto:huj_at_grandomics_dot_com).

## 14.4 Copyright

NextPolish is freely available for academic use and other non-commercial use.

## 14.5 Cite

Hu, Jiang, et al. “NextPolish: a fast and efficient genome polishing tool for long read assembly.” *Bioinformatics* (Oxford, England) (2019).

## 14.6 Limitations

NextPolish is designed for genomes assembled by long reads, so it assumes an input genome without gaps (N bases). Therefore, please split your genome assembly by its gaps and then link them back after polishing if your input contains gaps. Usually we scaffolded a genome using BioNano or Hic data after a polishing step.

## 14.7 Star

You can track updates by tab the `Star` button on the upper-right corner at the [github page](#).



**C**

check\_alive = auto  
    command line option, 25  
command line option  
    check\_alive = auto, 25  
    deltmp = yes, 24  
    genome = genome.fa, 25  
    genome\_size = auto, 25  
    hifi\_fofn = ./hifi.fofn, 26  
    hifi\_minimap2\_options = -x map-pb  
        -t {multithread\_jobs}, 26  
    hifi\_options = -min\_read\_len 1k  
        -max\_depth 100, 26  
    job\_id\_regex = auto, 25  
    job\_prefix = nextPolish, 24  
    job\_type = sge, 24  
    kill = auto, 25  
    lgs\_fofn = ./lgs.fofn, 25  
    lgs\_minimap2\_options = -x map-pb  
        -t {multithread\_jobs}, 26  
    lgs\_options = -min\_read\_len 1k  
        -max\_depth 100, 25  
    multithread\_jobs = 5, 24  
    parallel\_jobs = 6, 24  
    polish\_options = -p  
        {multithread\_jobs}, 25  
    rerun = 3, 24  
    rewrite = no, 24  
    sgs\_fofn = ./sgs.fofn, 25  
    sgs\_options = -max\_depth 100 -bwa,  
        25  
    submit = auto, 24  
    task = best, 24  
    use\_drmaa = no, 25  
    workdir = 01\_rundir, 25

**D**

deltmp = yes  
    command line option, 24

**G**

genome = genome.fa  
    command line option, 25  
genome\_size = auto  
    command line option, 25

**H**

hifi\_fofn = ./hifi.fofn  
    command line option, 26  
hifi\_minimap2\_options = -x map-pb -t  
    {multithread\_jobs}  
    command line option, 26  
hifi\_options = -min\_read\_len 1k  
    -max\_depth 100  
    command line option, 26

**J**

job\_id\_regex = auto  
    command line option, 25  
job\_prefix = nextPolish  
    command line option, 24  
job\_type = sge  
    command line option, 24

**K**

kill = auto  
    command line option, 25

**L**

lgs\_fofn = ./lgs.fofn  
    command line option, 25  
lgs\_minimap2\_options = -x map-pb -t  
    {multithread\_jobs}  
    command line option, 26  
lgs\_options = -min\_read\_len 1k  
    -max\_depth 100  
    command line option, 25

**M**

multithread\_jobs = 5

command line option,24

## P

parallel\_jobs = 6

command line option,24

polish\_options = -p {multithread\_jobs}

command line option,25

## R

rerun = 3

command line option,24

rewrite = no

command line option,24

## S

sgs\_fofn = ./sgs.fofn

command line option,25

sgs\_options = -max\_depth 100 -bwa

command line option,25

submit = auto

command line option,24

## T

task = best

command line option,24

## U

use\_drmaa = no

command line option,25

## W

workdir = 01\_rundir

command line option,25